

United 212 OXY PRO Professional In-N-Out utilizes the power of oxygen for improved cleaning and stain removal. Use this product on most hard surfaces like cement, brick, cinderblock walls, tile and grout. It cleans and removes dirt and stains caused by algae, mold and mildew as it penetrates through to brighten hard surfaces without hard scrubbing. Clings to vertical surfaces to maximize contact time.

United 212 OXY PRO Professional In-N-Out is:

Bio-based • Dye-Free • Non-Acid
Bleach Free • Fragrance-Free • Non-Caustic

DIRECTIONS:

Use undiluted for tough stains. Dilute up to 5:1 for light stains. Apply at temperatures above 32°F. Heavy stains may require longer contact time and agitation with a scrub brush; or a repeat treatment. When using on metal surfaces, particularly aluminum, brass or copper, limit contact time to 15-minute intervals and rinse thoroughly. Reapply and rinse again if needed. Chrome, stainless steel and galvanized steel can withstand longer contact times up to 3 hours before rinsing.

DO NOT USE ON PAINTED SURFACES. If unsure of compatibility test in a small inconspicuous area before use.

Indoor Use – Spray product on the surface to be treated. Let it remain in contact with surface for 10 to 20 minutes. You may wish to reapply product during that time to keep surface wet, depending upon conditions. Thoroughly rinse the surface with water to remove the dissolved stain and dirt particles.

Outdoor Use – Minimize product evaporation, by applying on cool dry surfaces early in the morning, on windless days when rain is not expected for 5 hours. Spray product onto surface and let it sit. Most outdoor applications will not require scrubbing or rinsing. Allow the rain and wind to help clean gradually and the stain will be removed in a few days. For faster results, agitate with a scrub brush. When rinsing is desired, a pressure washer with water may be best for rinsing from brick and cinder block surfaces.

For larger cleaning jobs, use a compression sprayer like United's A037 or A042. Protect plants from over-spray.

Approximate coverage: 150 to 400 square feet per gallon (undiluted), dependent on porosity of the surface and stain.

212

**OXY
PRO**

**Professional
In-N-Out**

UNITED
LABORATORIES

Manufactured and Sold Exclusively by:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DANGER: Causes skin irritation. Causes serious eye damage.



Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves, eye protection and face protection.

If exposed or concerned, immediately call a poison center or doctor/physician. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

ADDITIONAL FIRST AID INFORMATION:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove to fresh air.

IF SWALLOWED: Clean mouth with water and drink afterwards plenty of water.

CONTAINS (CAS#): Proprietary (Proprietary)

An SDS for this product is available through United's website. Please read the SDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

DANGER
KEEP OUT OF REACH OF CHILDREN.



Made in the USA